

LARGE COSMOPOLITAN® ELECTROL® Automatic Electric Projection Screen Model SPECIFICATION DATA DA-LITE SCREEN COMPANY, INC. 3100 North Detroit Street Post Office Box 137 Warsaw, Indiana 46581-0137 Phone: 574-267-8101 800-622-3737 Fax: 574-267-7804 Toll Free Fax: 877-325-4832 www.da-lite.com e-mail: info@da-lite.com

12' x 12', 200" DIAGONAL (120" x 160") AND LARGER SIZES (FOR SMALLER SIZES, REFER TO ADDITIONAL SPECIFICATION DATA SHEET)

SUGGESTED SPECIFICATIONS: ______ projection screen(s), ______ (H) x ______ (W), electrically operated 120 volt (60 Hz) not more than 2.4 amp. Shall have specially designed motor mounted inside the roller to be three wire with ground quick reversal type, oiled for life, with automatic thermal overload cut-out, integral gears, capacitor and an electric brake to prevent coasting. To have pre-set but adjustable limit switches to automatically stop picture surface in the "up" and "down" positions. The roller to be of aluminum. Screen fabric to be flame retardant and mildew resistant fiberglass with black masking borders standard. Bottom of fabric shall be formed into a pocket holding a metal rod. Case to be a two-piece design made of extruded aluminum with a white, lightly textured powder coat finish. End caps to be plastic with integrated junction box. To be complete with three position control switch with cover plate. Screen to be listed by Underwriters' Laboratories.

Matte White: Seamless in all standard sizes. High Contrast Matte White: Available in sizes where both dimensions do not exceed 10'.

VIDEO (NTSC 4:3) FORMAT DIMENSIONS (2" standard black drop at top)

Viewing Area		Nominal Diagonal		Overall Length of Case		Approx. Ship. Wt.	
НхW	Cm	In.	Cm	In.	Cm	Lbs.	Kg
120" x 160"	305 x 406	200"	508	1731/2"	441	210	95.3
123" x 164"	312 x 417	210"	533	177½"	451	225	102.1
141" x 188"	358 x 478	240"	610	2011/2"	512	254	115.2

HDTV (16:9) FORMAT DIMENSIONS (2" standard black drop at top)

Viewin	Viewing Area		Nominal Diagonal		Overall Length of Case		Approx. Ship. Wt.	
HxW	Cm	In.	Cm	In.	Cm	Lbs.	Kg	
92" x 164"	234 x 417	188"	478	177½"	451	215	97.5	
106" x 188"	269 x 478	216"	549	2011/2"	512	241	109.3	

WIDE (16:10) FORMAT DIMENSIONS

Viewing Area		Nominal Diagonal		Overall Length of Case		Approx. Ship. Wt.	
HxW	Cm	In.	Cm	In.	Cm	Lbs.	Kg
100" x 160"	254 x 406	189"	480	1731/2"	441	210	95.3
110" x 176"	279 x 447	208"	528	1891/2"	481	240	108.9
117½" x 188"	283 x 478	222"	564	201½"	512	254	115.2

SQUARE FORMAT DIMENSIONS

Siz	es	Overall Len	gth of Case	Approx. Ship. Wt.		
HxW	Cm	In.	Cm	Lbs.	Kg	
12' x 12'	366 x 366	1531⁄2"	390	194	88.0	
14' x 14'	427 x 427	1771⁄2"	451	229	103.9	
16' x 16'	488 x 488	201½"	512	263	119.3	

Overall case length dimensions $\pm \frac{1}{4}$ " (6mm).

Detail dimensional drawings, wiring diagrams and installation instructions available upon request.

Specifications subject to change without notice.

Custom formats and sizes available upon request.

 WHEN ORDERING, MARK APPROPRIATE SELECTIONS: Select size from charts on the other side. Select viewing surface: □ Matte White □ High Contrast Matte White 	Project:
GREENGUARD [®] and GREENGUARD [®] Children and Schools Certified.	Architect:
 Optional Accessories: Extra Drop available to lower picture area more than normal. Specify total drop at top (black or white) or at bottom (black or white). 16' maximum total 	Phone: Contractor: Phone:
surface height including picture area. No borders (Black masking borders standard).	Supervisor:
 Single Motor Low Voltage Control System (LVC) - external. Single Motor Low Voltage Control System (LVC) - built-in. Wireless Remote Control for LVC. 	Phone:Supplier:

Radio Frequency Remote

- □ Radio Frequency Range Extender available
- □ Infrared Remote
- Key Locking Cover Plate for 120 V Switch or LVC Switch.
- Key Operated Switch for 120 V only (Note: Cannot be used with LVC).
- 220 Volt (50 Hz) Motor.
- Video Projector Interface Control external.
- External SCB-100 RS-232 Serial Control Board □ NET-100 Ethernet-Serial Adapter
- Black case (white standard).

Project:	
Phone:	

COSMOPOLITAN® ELECTROL®

